

	T225B2100		Page 1/1
	4608166		12.5.2022
created:	JA	Note:	
approved:	Jl		

DECLARATION OF PERFORMANCE

1. **Unique identification code of the Product:** T225B2100 4608166
2. **Description of Product:** *Tehomet lighting columns*
3. **Intended using or uses of the construction:** *Construction and modernization of roads, streets, parks*
4. **Name and contact address of the manufacturer:** *Tehomet Oy, Nikkarintie 4, 51200 Kangasniemi, Finland, +358 15 337 7770*
5. **Assessment system and verification of constancy of performance of the construction product:** 1
6. **Notified Body:** *Inspecta Sertifiointi Oy, number 0416 performed determination of the product-type, initial inspection of the manufacturing plant and of factory production plant, continuous surveillance, assessment and evaluation of factory production control under system 1 and issued EC-Certificate of Conformity nr. 0416-CPR-3611-04 under EN 40-5:2002*

7. Declared performances:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical specification</i>
<i>Performance under vehicle impact</i>	<i>Class 0</i>	<i>EN40-5:2002</i>
<i>Corrosion protection</i>	<i>Hot dip galvanizing EN ISO 1461</i>	

8. Resistance to wind loads [m²]:

Weight of luminaire 20kg, deflection class 2

Terrain category		CAT1		CAT2		CAT3	
Partial load factor		A	B	A	B	A	B
wind	21m/s	0,19 m ²	0,3 m ²	0,3 m ²	0,43 m ²	0,52 m ²	0,69 m ²
	22m/s	0,14 m ²	0,24 m ²	0,24 m ²	0,35 m ²	0,43 m ²	0,59 m ²
	23m/s	0,1 m ²	0,19 m ²	0,18 m ²	0,29 m ²	0,36 m ²	0,5 m ²
	24m/s	0,06 m ²	0,15 m ²	0,14 m ²	0,24 m ²	0,3 m ²	0,43 m ²
	25m/s	0,04 m ²	0,11 m ²	0,1 m ²	0,19 m ²	0,25 m ²	0,36 m ²
	26m/s	0,02 m ²	0,09 m ²	0,07 m ²	0,15 m ²	0,2 m ²	0,31 m ²
	27m/s	0 m ²	0,07 m ²	0,04 m ²	0,12 m ²	0,16 m ²	0,26 m ²
	28m/s	0 m ²	0,05 m ²	0,02 m ²	0,09 m ²	0,12 m ²	0,22 m ²
	29m/s	0 m ²	0,03 m ²	0,01 m ²	0,07 m ²	0,09 m ²	0,18 m ²
	30m/s	0 m ²	0,02 m ²	0 m ²	0,05 m ²	0,06 m ²	0,14 m ²

Maximum base load:

M= 19,5 kNm

F= 2,7 kN

(Moment and shear at ground level)

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

Signed for and on behalf of the manufacturer by:

Joonas Innanen, Product Development and Engineering Manager

12.5.2022

Kangasniemi

