

		P125B1100 4608127		Page 1/1 12.5.2022
created:	JA	Note:		
approved:	Jl			

DECLARATION OF PERFORMANCE

- Unique identification code of the Product:** P125B1100 4608127
- Description of Product:** *Tehomet lighting columns*
- Intended using or uses of the construction:** *Construction and modernization of roads, streets, parks*
- Name and contact address of the manufacturer:** *Tehomet Oy, Nikkarintie 4, 51200 Kangasniemi, Finland, +358 15 337 7770*
- Assessment system and verification of constancy of performance of the construction product:** 1
- Notified Body:** *Inspecta Sertifiointi Oy, number 0416 performed determination of the product-type, initial inspection of the manufacturing plant and of factory production plant, continuous surveillance, assessment and evaluation of factory production control under system 1 and issued EC-Certificate of Conformity nr. 0416-CPR-3611-04 under EN 40-5:2002*

7. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Performance under vehicle impact	Class 0	EN40-5:2002
Corrosion protection	Hot dip galvanizing EN ISO 1461	

8. Resistance to wind loads [m²]:

Weight of luminaire 20kg, deflection class 2

Terrain category		CAT1		CAT2		CAT3	
Partial load factor		A	B	A	B	A	B
wind	21m/s	0,12 m ²	0,16 m ²	0,17 m ²	0,21 m ²	0,25 m ²	0,32 m ²
	22m/s	0,1 m ²	0,14 m ²	0,14 m ²	0,18 m ²	0,22 m ²	0,28 m ²
	23m/s	0,08 m ²	0,11 m ²	0,11 m ²	0,16 m ²	0,19 m ²	0,25 m ²
	24m/s	0,07 m ²	0,1 m ²	0,1 m ²	0,14 m ²	0,17 m ²	0,21 m ²
	25m/s	0,05 m ²	0,07 m ²	0,08 m ²	0,11 m ²	0,14 m ²	0,19 m ²
	26m/s	0,03 m ²	0,07 m ²	0,07 m ²	0,1 m ²	0,12 m ²	0,17 m ²
	27m/s	0,03 m ²	0,05 m ²	0,05 m ²	0,08 m ²	0,1 m ²	0,14 m ²
	28m/s	0,01 m ²	0,03 m ²	0,03 m ²	0,07 m ²	0,09 m ²	0,13 m ²
	29m/s	0 m ²	0,03 m ²	0,03 m ²	0,05 m ²	0,07 m ²	0,11 m ²
	30m/s	0 m ²	0,02 m ²	0,02 m ²	0,04 m ²	0,07 m ²	0,1 m ²

Maximum base load:

M= 13,6 kNm

F= 2,2 kN

(Moment and shear at ground level)

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

Signed for and on behalf of the manufacturer by:

Joonas Innanen, Product Development and Engineering Manager

12.5.2022

Kangasniemi

