


| | | | | |
|--|----|--------------|--|-----------|
|  | | S100B1080 | | Page 1/1 |
| | | 4608091 | | 12.5.2022 |
| created: | JA | Note: | | |
| approved: | Jl | | | |

DECLARATION OF PERFORMANCE

- Unique identification code of the Product:** S100B1080 4608091
- Description of Product:** *Tehomet lighting columns*
- Intended using or uses of the construction:** *Construction and modernization of roads, streets, parks*
- Name and contact address of the manufacturer:** *Tehomet Oy, Nikkarintie 4, 51200 Kangasniemi, Finland, +358 15 337 7770*
- Assessment system and verification of constancy of performance of the construction product:** 1
- Notified Body:** *Inspecta Sertifiointi Oy, number 0416 performed determination of the product-type, initial inspection of the manufacturing plant and of factory production plant, continuous surveillance, assessment and evaluation of factory production control under system 1 and issued EC-Certificate of Conformity nr. 0416-CPR-3611-04 under EN 40-5:2002*

7. Declared performances:

| <i>Essential characteristics</i> | <i>Performance</i> | <i>Harmonised technical specification</i> |
|---|--|---|
| <i>Performance under vehicle impact</i> | <i>Class 0</i> | <i>EN40-5:2002</i> |
| <i>Corrosion protection</i> | <i>Hot dip galvanizing EN ISO 1461</i> | |

8. Resistance to wind loads [m²]:

Weight of luminaire 20kg, deflection class 2

| Terrain category | | CAT1 | | CAT2 | | CAT3 | |
|---------------------|-------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| Partial load factor | | A | B | A | B | A | B |
| wind | 21m/s | 0,53 m ² | 0,66 m ² | 0,69 m ² | 0,83 m ² | 0,99 m ² | 1,18 m ² |
| | 22m/s | 0,46 m ² | 0,58 m ² | 0,6 m ² | 0,74 m ² | 0,87 m ² | 1,06 m ² |
| | 23m/s | 0,41 m ² | 0,52 m ² | 0,53 m ² | 0,66 m ² | 0,78 m ² | 0,95 m ² |
| | 24m/s | 0,36 m ² | 0,46 m ² | 0,47 m ² | 0,59 m ² | 0,7 m ² | 0,85 m ² |
| | 25m/s | 0,32 m ² | 0,41 m ² | 0,42 m ² | 0,53 m ² | 0,62 m ² | 0,77 m ² |
| | 26m/s | 0,28 m ² | 0,36 m ² | 0,38 m ² | 0,47 m ² | 0,56 m ² | 0,69 m ² |
| | 27m/s | 0,25 m ² | 0,32 m ² | 0,33 m ² | 0,42 m ² | 0,5 m ² | 0,62 m ² |
| | 28m/s | 0,22 m ² | 0,29 m ² | 0,3 m ² | 0,38 m ² | 0,45 m ² | 0,57 m ² |
| | 29m/s | 0,19 m ² | 0,26 m ² | 0,26 m ² | 0,35 m ² | 0,41 m ² | 0,52 m ² |
| | 30m/s | 0,17 m ² | 0,24 m ² | 0,24 m ² | 0,31 m ² | 0,37 m ² | 0,47 m ² |

Maximum base load:

M= 9,8 kNm

F= 1,9 kN

(Moment and shear at ground level)

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

Signed for and on behalf of the manufacturer by:

Joonas Innanen, Product Development and Engineering Manager

12.5.2022

Kangasniemi

