

		S200C312K 4607836		Page 1/1 12.5.2022
created:	JA	Note:		
approved:	Jl			

DECLARATION OF PERFORMANCE

- Unique identification code of the Product:** S200C312K 4607836
- Description of Product:** *Tehomet lighting columns*
- Intended using or uses of the construction:** *Construction and modernization of roads, streets, parks*
- Name and contact address of the manufacturer:** *Tehomet Oy, Nikkarintie 4, 51200 Kangasniemi, Finland, +358 15 337 7770*
- Assessment system and verification of constancy of performance of the construction product:** 1
- Notified Body:** *Inspecta Sertifiointi Oy, number 0416 performed determination of the product-type, initial inspection of the manufacturing plant and of factory production plant, continuous surveillance, assessment and evaluation of factory production control under system 1 and issued EC-Certificate of Conformity nr. 0416-CPR-3611-04 under EN 40-5:2002*

7. Declared performances:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical specification</i>
<i>Performance under vehicle impact</i>	<i>Class 0</i>	<i>EN40-5:2002</i>
<i>Corrosion protection</i>	<i>Hot dip galvanizing EN ISO 1461</i>	

8. Resistance to wind loads [m²]:

Weight of luminaire 20kg, deflection class 2

Terrain category		CAT1		CAT2		CAT3	
Partial load factor		A	B	A	B	A	B
wind	21m/s	1,14 m ²	1,32 m ²	1,4 m ²	1,58 m ²	1,92 m ²	2,15 m ²
	22m/s	1,01 m ²	1,18 m ²	1,24 m ²	1,42 m ²	1,71 m ²	1,92 m ²
	23m/s	0,91 m ²	1,07 m ²	1,11 m ²	1,28 m ²	1,54 m ²	1,74 m ²
	24m/s	0,82 m ²	0,97 m ²	1 m ²	1,16 m ²	1,38 m ²	1,57 m ²
	25m/s	0,74 m ²	0,88 m ²	0,9 m ²	1,06 m ²	1,24 m ²	1,42 m ²
	26m/s	0,67 m ²	0,8 m ²	0,82 m ²	0,96 m ²	1,13 m ²	1,3 m ²
	27m/s	0,6 m ²	0,73 m ²	0,74 m ²	0,88 m ²	1,03 m ²	1,19 m ²
	28m/s	0,55 m ²	0,67 m ²	0,67 m ²	0,81 m ²	0,93 m ²	1,1 m ²
	29m/s	0,5 m ²	0,62 m ²	0,62 m ²	0,75 m ²	0,86 m ²	1,01 m ²
	30m/s	0,46 m ²	0,57 m ²	0,57 m ²	0,69 m ²	0,79 m ²	0,93 m ²

Maximum base load:

M= 28,3 kNm

F= 3,4 kN

(Moment and shear at ground level)

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

Signed for and on behalf of the manufacturer by:

Joonas Innanen, Product Development and Engineering Manager

12.5.2022

Kangasniemi

